

1.	VESSEL DESCRIPTION		
1.1	Date updated:		
1.2	Vessel's name:	MT TRESTA STAR	
1.3	IMO number:	9869629	
1.4	Vessel's previous name(s) and date(s) of change:		
1.5	Date delivered:	28 March 2019	
1.6	Builder (where built):		
1.7	Flag:	Mauritius	
1.8	Port of Registry:	Port Louis	
1.9	Call sign:	3BTK	
1.10	Vessel's satcom phone number:		
	Vessel's fax number:		
	Vessel's telex number:	46500334 / 46500333	
	Vessel's email address:	master.trestastar@gmail.com	
1.11	Type of vessel:	Oil tanker/M.S Class 9 Tanker	
1.12	Type of hull:	Double Hull	
Classification			
1.13	Classification society:	I.R.S	
1.14	Class notation:	IRS/+SUL,OIL TANKER, ESP,"FOR CARRIAGE OF OIL OFFLASH POINT ABOVE 60", INWATER SURVEY, +IY	
1.15	If Classification society changed, name of previous society:		
1.16	If Classification society changed, date of change:		
1.17	IMO type, if applicable:		
1.18	Does the vessel have ice class? If yes, state what level:		
1.19	Date / place of last dry-dock:		
1.20	Date next dry dock due		
1.21	Date of last special survey / next survey due:		
1.22	Date of last annual survey:		
1.23	If ship has Condition Assessment Program (CAP), what is the latest overall rating:		
1.24	Does the vessel have a statement of compliance issued under the provisions of the Condition Assessment Scheme (CAS): If yes, what is the expiry date?		
Dimensions			
1.25	Length Over All (LOA):	70.340 Metres	
1.26	Length Between Perpendiculars (LBP):	69.892Metres	
1.27	Extreme breadth (Beam):	15.995 Metres	
1.28	Moulded depth:	6.0180 Metres	
1.29	Keel to Masthead (KTM) / KTM in collapsed condition (if applicable):		
1.30	Bow to Center Manifold (BCM) / Stern to Center Manifold (SCM):		
1.31	Distance bridge front to center of manifold:		
1.32	Parallel body distances:	Lightship	Normal Ballast Summer Dwt
	Forward to mid-point manifold:		
	Aft to mid-point manifold:		
	Parallel body length:		
1.33	FWA at summer draft / TPC immersion at summer draft:		
1.34	What is the max height of mast above waterline (air draft)	Full Mast	Collapsed Mast
	Lightship:	50.0	
	Normal ballast:	3838	
	At loaded summer deadweight:		
Tonnages			
1.35	Net Tonnage:	695	
1.36	Gross Tonnage / Reduced Gross Tonnage (if applicable):	2021	
1.37	Suez Canal Tonnage - Gross (SCGT) / Net (SCNT):		

1.38	Panama Canal Net Tonnage (PCNT):				N/A
Loadline Information					
1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	1868 m	4.15m	2918.50T	4021.45T
	Winter:	1958m	4.06m	2815.68T	3918.59T
	Tropical:	1778m	4.24m	2981.30T	4084.22T
	Lightship:	4718m	1.30m		1091.60T
	Normal Ballast Condition:	3838m	2.18m	851.77T	1954.63T
1.40	Does vessel have multiple SDWT?				
1.41	If yes, what is the maximum assigned deadweight?				
Ownership and Operation					
1.42	Registered owner - Full style:			Tresta Trading Ltd, The Ground IBL BUSINESS PARK, ROYAL ROAD, CASSIS, REPUBLIC OF MAURITIUS	
1.43	Technical operator - Full style:			AMBA SHIPPING & LOGISTICS PVT LTD, NAVI MUMBAI, INDIA	
1.44	Commercial operator - Full style:				
1.45	Disponent owner - Full style:				

2.	CERTIFICATION	Issued	Last Annual or Intermediate	Expires	
2.1	Safety Equipment Certificate:				
2.2	Safety Radio Certificate:				
2.3	Safety Construction Certificate:				
2.4	Loadline Certificate:				
2.5	International Oil Pollution Prevention Certificate (IOPPC):				
2.6	Safety Management Certificate (SMC):				
2.7	Document of Compliance (DOC):				
2.8	USCG (specify: COC, LOC or COI): COC				
2.9	Civil Liability Convention Certificate (CLC):		-		
2.10	Civil Liability for Bunker Oil Pollution Damage Convention Certificate (CLBC):		-		
2.11	U.S. Certificate of Financial Responsibility (COFR):				
2.12	Certificate of Fitness (Chemicals):				
2.13	Certificate of Fitness (Gas):				
2.14	Certificate of Class:				
2.15	International Ship Security Certificate (ISSC):				
2.16	International Sewage Pollution Prevention Certificate (ISPPC)		-		
2.17	International Air Pollution Prevention Certificate (IAPP):				
Documentation					
2.18	Does vessel have all updated publications as listed in the Vessel Inspection Questionnaire, Chapter 2- Question 2.24, as applicable:				
2.19	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:				

3.	CREW MANAGEMENT	
3.1	Nationality of Master:	
3.2	Nationality of Officers:	
3.3	Nationality of Crew:	
3.4	If Officers/Crew employed by a Manning Agency - Full style:	
3.5	What is the common working language onboard:	
3.6	Do officers speak and understand English:	
3.7	In case of Flag Of Convenience, is the ITF Special Agreement on board:	

4.	HELICOPTERS	
4.1	Can the ship comply with the ICS Helicopter Guidelines:	
4.2	If Yes, state whether winching or landing area provided:	

5.	FOR USA CALLS	
5.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter:	
5.2	Qualified individual (QI) - Full style:	
5.3	Oil Spill Response Organization (OSRO) -Full style:	
5.4	Has technical operator signed the SCIA / C-TPAT agreement with US customs concerning drug smuggling:	

6.	CARGO AND BALLAST HANDLING	
Double Hull Vessels		
6.1	Is vessel fitted with centerline bulkhead in all cargo tanks:	
6.2	If Yes, is bulkhead solid or perforated:	
Cargo Tank Capacities		
6.3	Capacity (98%) of each natural segregation with double valve (specify tanks):	2630.28 Cu.M

6.4	Total cubic capacity (98%, excluding slop tanks):	26.30.28Cu.M		
6.5	Slop tank(s) capacity (98%):			
6.6	Residual/Retention oil tank(s) capacity (98%), if applicable:			
6.7	Does vessel have Segregated Ballast Tanks (SBT) or Clean Ballast Tanks (CBT):			
SBT Vessels				
6.8	What is total capacity of SBT?			
6.9	What percentage of SDWT can vessel maintain with SBT only:			
6.10	Does vessel meet the requirements of MARPOL Annex I Reg 18.2: (previously Reg 13.2)			
Cargo Handling				
6.11	How many grades/products can vessel load/discharge with double valve segregation:			
6.12	Maximum loading rate for homogenous cargo per manifold connection:			
6.13	Maximum loading rate for homogenous cargo loaded simultaneously through all manifolds:			
6.14	Are there any cargo tank filling restrictions. If yes, please specify:			
Pumping Systems				
6.15	Pumps:	No.	Type	Capacity
	Cargo: Slop tanks	4		150/250 M³/Hr
	Stripping:			
	Eductors:			
	Ballast:	2		60 M³/Hr
6.16	How many cargo pumps can be run simultaneously at full capacity:			
6.17	Is ship fitted with a Cargo Control Room (CCR):			
6.18	Can tank innage / ullage be read from the CCR:			
Gauging and Sampling				
6.19	Can ship operate under closed conditions in accordance with ISGOTT:			
6.20	What type of fixed closed tank gauging system is fitted:			
6.21	Are overfill (high-high) alarms fitted? If Yes, indicate whether to all tanks or partial:			
Vapor Emission Control				
6.22	Is a vapor return system (VRS) fitted:			
6.23	Number/size of VRS manifolds (per side):			
Venting				
6.24	State what type of venting system is fitted:			
Cargo Manifolds				
6.25	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment':			
6.26	What is the number of cargo connections per side:			
6.27	What is the size of cargo connections:			
6.28	What is the material of the manifold:			
Manifold Arrangement				
6.29	Distance between cargo manifold centers:			
6.30	Distance ships rail to manifold:			
6.31	Distance manifold to ships side:			
6.32	Top of rail to center of manifold:			
6.33	Distance main deck to center of manifold:			
6.34	Manifold height above the waterline in normal ballast / at SDWT condition:			

6.35	Number / size reducers:			
Stern Manifold				
6.36	Is vessel fitted with a stern manifold:			
6.37	If stern manifold fitted, state size:			
Cargo Heating				
6.38	Type of cargo heating system?			
6.39	If fitted, are all tanks coiled?			
6.40	If fitted, what is the material of the heating coils:			
6.41	Maximum temperature cargo can be loaded/maintained:			
Tank Coating				
6.42	Are cargo, ballast and slop tanks coated?	Coated	Type	To What Extent
	Cargo tanks:	None		
	Ballast tanks:	Yes	Epoxy-International	
	Slop tanks:			
6.43	If fitted, what type of anodes are used:			

7.	INERT GAS AND CRUDE OIL WASHING			
7.1	Is an Inert Gas System (IGS) fitted:			
7.2	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:			
7.3	Is a Crude Oil Washing (COW) installation fitted:			

8.	MOORING					
8.1	Mooring wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
8.2	Wire tails		Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
8.3	Mooring ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
8.4	Other mooring lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
8.5	Mooring winches		No.		# Drums	Brake Capacity
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:				Double Drums	
8.6	Mooring bitts				No.	SWL
	Forecastle:					
	Main deck fwd:					

		Main deck aft:		
		Poop deck:		
8.7	Closed chocks and/or fairleads of enclosed type		No.	SWL
		Forecastle:		
		Main deck fwd:		
		Main deck aft:		
		Poop deck:		

Emergency Towing System

8.8	Type / SWL of Emergency Towing system forward:		
8.9	Type / SWL of Emergency Towing system aft:		

Anchors

8.10	Number of shackles on port cable:		
8.11	Number of shackles on starboard cable:		

Escort Tug

8.12	What is SWL and size of closed chock and/or fairleads of enclosed type on stern:		
8.13	What is SWL of bollard on poopdeck suitable for escort tug:		

Bow/Stern Thruster

8.14	What is brake horse power of bow thruster (if fitted):		
8.15	What is brake horse power of stern thruster (if fitted):		

Single Point Mooring (SPM) Equipment

8.16	Does vessel comply with the latest edition of OCIMF 'Recommendations for Equipment Employed in the Mooring of Vessels at Single Point Moorings (SPM)':		
8.17	Is vessel fitted with chain stopper(s):		
8.18	How many chain stopper(s) are fitted:		
8.19	State type of chain stopper(s) fitted:		
8.20	Safe Working Load (SWL) of chain stopper(s):		
8.21	What is the maximum size chain diameter the bow stopper(s) can handle:		
8.22	Distance between the bow fairlead and chain stopper/bracket:		
8.23	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:		

Lifting Equipment

8.24	Derrick / Crane description (Number, SWL and location):		
8.25	What is maximum outreach of cranes / derricks outboard of the ship's side:		

Ship To Ship Transfer (STS)

8.26	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum or Liquefied Gas, as applicable):		
------	---	--	--

9. MISCELLANEOUS

Engine Room

9.1	What type of fuel is used for main propulsion?		
9.2	What type of fuel is used in the generating plant?		
9.3	Capacity of bunker tanks - IFO and MDO/MGO:		
9.4	Is vessel fitted with fixed or controllable pitch propeller(s)?		

Insurance

9.5	P & I Club - Full Style:		
9.6	P & I Club coverage - pollution liability coverage:		

Port State Control

9.7	Date and place of last Port State Control inspection:		
9.8	Any outstanding deficiencies as reported by any Port State Control:		
9.9	If yes, provide details:		

Recent Operational History		
9.10	Has vessel been involved in a pollution, grounding, serious casualty or collision incident during the past 12 months? If yes, full description:	
9.11	Last three cargoes / charterers / voyages (Last / 2nd Last / 3rd Last):	
Vetting		
9.12	Date/Place of last SIRE Inspection:	
9.13	Date/Place of last CDI Inspection:	
9.14	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: <i>* Blanket "approvals" are no longer given by Oil Majors and ships are accepted for the voyage on a case by case basis.</i>	

Version 3 ([INTERTANKO](#) /)